slow_key_setup1 Project Status (06/16/2011 - 16:11:18)				
Project File:	bflike1.xise	Parser Errors:	No Errors	
Module Name:	slow_key_setup1	Implementation State:	Placed and Routed	
Target Device:	xc6slx45-3fgg484	• Errors:	No Errors	
<b>Product Version:</b>	ISE 13.1	• Warnings:	338 Warnings (37 new)	
Design Goal:	Balanced	<ul><li>Routing Results:</li></ul>	All Signals Completely Routed	
Design Strategy:	Xilinx Default (unlocked)	• Timing Constraints:	X 1 Failing Constraint	
<b>Environment:</b>	System Settings	• Final Timing Score:	1241 (Timing Report)	

Device Utilization Summary					
Slice Logic Utilization	Used	Available	Utilization	Note(s)	
Number of Slice Registers	290	54,576	1%		
Number used as Flip Flops	3				
Number used as Latches	287				
Number used as Latch-thrus	0				
Number used as AND/OR logics	0				
Number of Slice LUTs	1,423	27,288	5%		
Number used as logic	1,423	27,288	5%		
Number using O6 output only	1,272				
Number using O5 output only	0				
Number using O5 and O6	151				
Number used as ROM	0				
Number used as Memory	0	6,408	0%		
Number of occupied Slices	443	6,822	6%		
Number of LUT Flip Flop pairs used	1,423				
Number with an unused Flip Flop	1,134	1,423	79%		
Number with an unused LUT	0	1,423	0%		
Number of fully used LUT-FF pairs	289	1,423	20%		
Number of unique control sets	36				
Number of slice register sites lost to control set restrictions	14	54,576	1%		
Number of bonded <u>IOBs</u>	24	316	7%		
IOB Latches	10				
Number of RAMB16BWERs	0	116	0%		
Number of RAMB8BWERs	0	232	0%		
Number of BUFIO2/BUFIO2_2CLKs	0	32	0%		
Number of BUFIO2FB/BUFIO2FB_2CLKs	0	32	0%		
Number of BUFG/BUFGMUXs	1	16	6%		
Number used as BUFGs	1				
Number used as BUFGMUX	0				
Number of DCM/DCM_CLKGENs	0	8	0%		
Number of ILOGIC2/ISERDES2s	0	376	0%		
Number of IODELAY2/IODRP2/IODRP2_MCBs	0	376	0%		
Number of OLOGIC2/OSERDES2s	10	376	2%		
Number used as OLOGIC2s	10				
Number used as OSERDES2s	0				
Number of BSCANs	0	4	0%		
Number of BUFHs	0	256	0%		

Number of BUFPLLs	0	8	0%	
Number of BUFPLL_MCBs	0	4	0%	
Number of DSP48A1s	0	58	0%	
Number of ICAPs	0	1	0%	
Number of MCBs	0	2	0%	
Number of PCILOGICSEs	0	2	0%	
Number of PLL_ADVs	0	4	0%	
Number of PMVs	0	1	0%	
Number of STARTUPs	0	1	0%	
Number of SUSPEND_SYNCs	0	1	0%	
Average Fanout of Non-Clock Nets	5.49			

Performance Summary [-]					
Final Timing Score:	1241 (Setup: 1241, Hold: 0)	Pinout Data:	Pinout Report		
Routing Results:	All Signals Completely Routed	Clock Data:	Clock Report		
Timing Constraints:	X 1 Failing Constraint				

Detailed Reports					<u>[-]</u>
Report Name	Status	Generated	Errors	Warnings	Infos
Synthesis Report	Current	qui 16. jun 16:09:15 2011	0	301 Warnings (0 new)	1 Info (0 new)
Translation Report	Current	qui 16. jun 16:09:21 2011	0	0	0
Map Report	Current	qui 16. jun 16:10:23 2011	0	37 Warnings (37 new)	6 Infos (0 new)
Place and Route Report	Current	qui 16. jun 16:10:59 2011	0	0	4 Infos (0 new)
Power Report					
Post-PAR Static Timing Report	Current	qui 16. jun 16:11:16 2011	0	0	3 Infos (0 new)
Bitgen Report	Out of Date	seg 30. mai 16:27:58 2011	0	0	0

Secondary Reports			
Report Name	Status	Generated	
ISIM Simulator Log	Out of Date	seg 13. jun 18:44:17 2011	
WebTalk Report	Out of Date	seg 30. mai 16:27:58 2011	
WebTalk Log File	Out of Date	seg 30. mai 16:28:20 2011	

**Date Generated:** 06/16/2011 - 16:11:18